

HR-16000-SB Series

HR-16000-SB-M Monochrome
HR-16000-SB-C Color

| Back-illuminated pixel structure



Back-illuminated 16.13MP 10GigE camera with Sony Pregius S IMX532 CMOS sensor

HR-16000-SB features the Sony Pregius S IMX532 sensor. The Sony Pregius S technology features back-illuminated pixel structure that delivers distortion-free, high imaging performance and miniaturization. At full resolution (5320 x 3032) you get up to 77 frames per second. Its ultra high-speed SFP+ 10GigE interface offers many benefits including low-cost accessories, low CPU overhead, low latency, low jitter, and accurate multi-camera synchronization using IEEE1588. In addition, SFP+ 10GigE offers three supported cabling options for cable lengths from 1M to 10KM.

Benefits

- » High-speed SFP+ 10GigE interface
- » Back-illuminated pixel structure
- » 10x the speed of GigE
- » Ultra high data/frame rates
- » GigE Vision® and Genicam™ compliant
- » Optional IP67 housing

Applications

- » Industrial inspection
- » Automation
- » Intelligent Transportation Systems
- » Logistics
- » Virtual reality
- » Volumetric capture
- » Referee Assist

Specifications

Sensor	Sony IMX532
R	5320 x 3032
Megapixels	16.13 MP
Sensor Type	1.1 CMOS
Max Frame Rate	77 fps @ 8-bit 50 fps @ 12-bit
Cell Size	2.74µm x 2.74µm
Standard Mount	C Mount
Region	Global
Bit Depth	8 & 12 bit
GPIO / Triggering	3 in, 3 out are, External (Pulse or Edge)
Interface	SFP+ 10GigE
Exposure/Integra	5µs-1s
Dynamic Range	74 dB
Monochrome Modes	Mono8, Mono12, Mono12Packed
Color Modes	RGB8, BGR8, YUV411, YUV422, YUV444
Raw Modes	BayerRG8, BayerRG12, BayerRG12Packed
Operating System	Win10 (64 bit), Linux (64 bit)
Compliance	CE, FCC, RoHS, WEEE, GigE Vision, GenICam
Power Requirements	9W, 12V
Operating Temperature	0C- 45C
Storage Temperature	-30C to +60C
Dimensions & Weight	997 x 66 x 52- 500g
Warranty	2 Years

*all minimum exposure specs can vary from what is listed based on the limitations from the manufacturer.

Mechanical drawings

