



HT-8000-SB Series

HT-8000-SB-M Monochrome HT-8000-SB-C Color

Back-illuminated pixel structure





GEN**<i>**CAM





Back-illuminated 8.1MP 10GigE camera with Sony Pregius S IMX536 CMOS sensor

HT-8000-SB features the Sony Pregius S IMX536 sensor. The Sony Pregius S technology features back-illuminated pixel structure that delivers distortion-free, high imaging performance and miniaturization. At full resolution (2840 x 2840) you get up to 145 frames per second. With its 10GBaseT interface, sleek smaller case and CAT6A connection, this camera has the familiarity of GigE but with 10x the speed. Using CAT6A cabling, you can get cable lengths from 1 meter up to 100 meters. The HT-8000-SB offers multi-camera synchronization at <1µs, low CPU overhead, and excellent priceperformance ratio.

Benefits

- » High-speed RJ45 10GBaseT interface
- » 10x the speed of GigE
- » GigE Vision[®] and Genicam[™] compliant
- » Back-illuminated pixel structure

Applications

- » Industrial inspection
- » Automation
- » Intelligent Transportation Systems
- » Logistics
- » Virtual reality
- » Volumetric capture
- » Referee Assist

Specifications

Sensor	Sony IMX536
Resolution	2840 x 2840
Megapixels	8.1 MP
Sensor Type	2/3 CMOS
Max Frame Rate	145 fps @ 8-bit 100 fps @ 12-bit
Cell Size	2.74µm x 2.74µm
Standard Mount	C Mount
Shutter	Global
Bit Depth	8 & 12 bit
GPIO / Triggering	3 in, 3 out Software, External (Pulse or Edge)
Interface	RJ45 10GBaseT
Exposure/Integration*	5µs-1s
Dynamic Range	74 dB
Monochrome Modes	Mono8, Mono12, Mono12Packed
Color Modes	RGB8, BGR8, YUV411, YUV422, YUV444
Raw Modes	BayerRG8, BayerRG12, BayerRG12Packed
Operating System	Win10 (64 bit), Linux (64 bit)
Compliance	CE, FCC, RoHS, WEEE, GigE Vision, GenICam
Power Requirements	9W, 12V
Operating Temperature	0C- 45C
Storage Temperature	-30C to +60C
Dimensions & Weight	88 x 58 x 39- 275g
Warranty	2 Years

*all minimum exposure specs can vary from what is listed based on the limitations of each sensor as per notice from the manufacturer.



Mechanical drawings









