




1.1" 1.8/35mm C		1.1"	1"	2/3"
FOCAL LENGTH		f=35mm		
F-NUMBER		F=1.8-16		
PICTURE SIZE		10.6×14.1mm	9.6×12.8mm	6.6×8.8mm
ANGLE OF VIEW (∞)	VER. ANGLE	16.7°	15.2°	10.5°
	HOR. ANGLE	22.1°	20.2°	14.0°
	DIA. ANGLE	27.5°	25.1°	17.4°
DISTORTION (TV)		0.01%	0.01%	0.01%
FIELD OF VIEW (MINIMUM FOCUS DISTANCE)	VER.	63mm	57mm	39mm
	HOR.	84mm	76mm	52mm
	DIA.	104mm	95mm	65mm
MINIMUM FOCUS DISTANCE		0.2m		
FLANGE BACK		17.526mm in air		
BACK FOCUS		15.5mm in air		
FILTER SCREW SIZE		M40.5×0.5		
FRONT/REAR EFFECTIVE DIA.		FRONT φ33.4mm		REAR φ16.2mm
MOUNT		C-MOUNT		
EXIT PUPIL		-40.0mm		
TEMPERATURE RANGE		-10~+50°C		
STORAGE TEMPERATURE RANGE		-20~+60°C		
RESOLUTION CENTER/CORNER		CENTER 200lp/mm		CORNER 100lp/mm
WEIGHT		205g		

NOTE: Specifications and availability are subject to change without notice

注) 本仕様については、予告なしに変更する場合があります。

		尺 度	1/1	工場 番号	LM35FC
		機 種 名	1.1" F1.8 f=35mm		
2019.12.02	表記誤記修正	機 種 番	LM35FC24M 外観図		
2018.02.09	印字誤記修正				
2017.09.15	作成年月日				