

# LR-16KG35 Line Scan

LR-16KG35-M Monochrome

LR-16KG35-C Color



## LR-16KG35: 10GigE line-scan camera with Gpixel GL3516

PACE LR-16KG35 features the Gpixel GL3516 CMOS sensor. LR-16KG35 comes with a resolution of 16Kx2 pixels and a line rate of: Single Line - 70KHz, Trilinear - 23KHz. This enables high-speed and low-noise image capture at 16K vision, ensuring all your inspection, sorting and production control requirements are met. Its 10GigE SFP+ interface allows cable lengths from 1M up to 10KM without the need for costly fiber converters/repeaters.

### Benefits

- » High-speed 10GigE via SFP+
- » 10x the speed of GigE
- » GigE Vision® and GenICam™ compliant

### Applications


- » Industrial Inspection
- » Printing Inspection
- » Label Inspection
- » Film Inspection
- » PCB Inspection
- » Automotive Inspection
- » Food Sorting and Grading
- » Pharmaceutical Inspection

## Specifications


Sensor	GL3516
Resolution	16Kx2
Line Scan Mode	Single line - 70KHz Trilinear - 23KHz
Sensor Scanning Width	57.344mm
Cell Size	3.5x3.5µm
Standard Mount	M72
Shutter	Global
Bit Depth	8 & 10 bit
GPIO / Triggering	2 in, 1 out, Encoder A/B in
Interface	10GigE SFP+
Exposure/Integration*	1µs-1s
Dynamic Range	66dB
Monochrome Modes	Mono8, Mono10, Mono10Packed
Color Modes	RGB
Corrections	Flat shading (dark, lit), Spatial
Operating System	Win 7, 8, 10, Linux (64bit)
Compliance	CE, FCC, RoHS, WEEE, GigE Vision, GenICam
Power Requirements	8W
Operating Temperature	0C - 45C
Storage Temperature	-30C to +60C
Dimensions & Weight	97 x 58 x 60 - 395g
Warranty	2 Years

\*all minimum exposure specs can vary from what is listed based on the limitations of each sensor as per notice from the manufacturer.

## Mechanical drawings



## Spectral Sensitivity



### Any Questions?

1-866-780-6082

[sales@emergentvisiontec.com](mailto:sales@emergentvisiontec.com)

<https://emergentvisiontec.com>